

IN STOCK NOW!

Jones Stephens Corp. PlumBest®

New!

PlumBite

IN STOCK NOW!

PlumBite fittings are a heat free method for joining Copper, CPVC and PEX tube and are designed to save time and money on installations.

PlumBite fittings are designed and certified to join PEX tubing. In order to make an effective joint with PEX tube, the included tube liner must be used. Do not substitute any other manufacturer's liner.



TUBE SIZE	INSERTION DEPTH
1/2"	31/32"
3/4"	1-1/8"

FEATURES AND BENEFITS:

- ➔ PUSH FIT
- ➔ REDUCED INSTALLATION TIME
- ➔ IDEAL FOR SERVICE AND REPAIR
- ➔ 1/2" AND 3/4" DIAMETER POTABLE WATER SYSTEMS
- ➔ "O-RING" DESIGN FOR LEAK FREE SEALS
- ➔ EPDM O-RING SEAL
- ➔ 316 STAINLESS STEEL RETAINING RING
- ➔ DESIGNED FOR USE WITH ASTM B88 HARD DRAWN AND ANNEALED COPPER TUBE, TYPE K, L, OR M, IN THE 1/2" THROUGH 3/4" SIZE RANGE; CPVC WATER TUBE PER ASTM D2846/2846M AND PEX TUBE THAT MEETS THE REQUIREMENTS OF ASTM F876 & F877
- ➔ OPERATE AT TEMPERATURES FROM 0° TO 250° F AT A MAXIMUM WORKING PRESSURE OF 200 PSI.
- ➔ SOLD IN BAG QUANTITY ONLY

JSC PART #	DESCRIPTION	SOLD IN BAG QTY. ONLY	
		BAG / CTN.	LIST PRICE
C76-500	1/2" COUPLING	10/150	7.78
C76-501	3/4" COUPLING	5/100	8.86
C76-502	3/4" x 1/2" REDUCER COUPLING	5/100	8.47
C76-503	1/2" C x F ADAPTER	10/100	5.79
C76-504	3/4" C x F ADAPTER	5/100	6.35
C76-505	1/2" C x M ADAPTER	10/200	5.69
C76-506	3/4" C x M ADAPTER	5/100	6.35
C76-507	1/2" x 1/2" 90° ELL	10/150	8.15
C76-508	3/4" x 3/4" 90° ELL	5/80	9.80
C76-509	1/2" DROP EAR 90° ELL	5/100	6.95
C76-510	1/2" EQUAL TEE	10/100	11.06
C76-511	3/4" EQUAL TEE	5/50	13.18
C76-512	3/4" x 3/4" x 1/2" TEE	5/50	12.64
C76-515	1/2" CAP	10/200	6.50
C76-516	3/4" CAP	5/150	8.15
C76-520	1/2" REMOVAL TOOL	1/1	.87
C76-521	3/4" REMOVAL TOOL	1/1	.96

Type of Service	System Operating Conditions
FLUIDS	
Hot and Cold Potable Water	32° F to 200° F, max. 200 PSI
Potable Water System Flushing	Compliant with major plumbing codes
Chilled Water w/ corrosion inhibitors	0° F to 250° F, max. 200 PSI
	Ethylene Glycol - 50% max. concentration
	Propylene Glycol - 50% max. concentration
Hydronic Heating	0° F to 250° F, max. concentration
	Ethylene Glycol - 50% max. concentration
	Propylene Glycol - 50% max. concentration
Rainwater/Greywater	32° F to 250° F, max. 200 PSI



PHONE: 1-800-355-6637 (35-JONES)